



BESCO 200HD TWO YARD STATIONARY COMPACTOR



- Heavy duty construction that exceeds industry standards
 - Guide system accessible for replacement as needed
- Bolt on fabricated options for adapting to a variety of installation choices
 - ETL & UL Listed / ANSI Z245.5 compliant
- Anti-corrosive aluminum ceramic coating on turnbuckle with solid dry film coating for lubrication on the threads
- Powder coating on all structural parts for a more durable and long lasting finish as well as anti-corrosive properties
 - Precision built components with guaranteed trouble-free replacement
 - [2-Year Extended Warranty](#)

200HD Specifications

- Manufacturing Rating...2.0 cubic yards
- Wastec Rating.....1.51 cubic yards
- Clear Top Opening.....42" L X 58" W
- Ram Face.....59 15/16" W X 28" H
- Ground Height.....15.5"
- Cycle Time.....63 seconds
- Total Maximum Compact Force..56,520 LBS
- Maximum Ram Face Pressure..33.6 PSI
- Ram Face Penetration.....14"

Electrical

- Motor 15 HP, 208-230/ 460V, 3PH
- Controls 120V AC
- UL Listed

Overall Dimensions

- Length 120 " Width: 76.5" Height: 60.5"

Hydraulic

- Pump.....10.5 GPM
- Reservoir.....30 gallons
- Normal System Pressure.....1,700 PSI
- Maximum System Pressure..2,400 PSI
- Cylinder Bore.....6"
- Rod Diameter.....4"
- Stroke.....56"

Structural

- Sides.....1/4"
- Vertical Structural Support....4" X 4" X 3/8" angle
- Top Rail and Bottom Support..4" X 5/8" FB
- Charge Box Floor.....1/2"
- Ram Face1/2"
- Ram Top.....1/4"
- Ram Bottom.....3/8"
- Ram Sides.....3/8"
- Breaker Bar..... 6" X 8" X 3/4"



"The Recycling and Waste Solutions People"

1160 WEST TRINDLE ROAD SUITE C

MECHANICSBURG, PA 17055

717-691-7490

717-691-7495 – FAX

www.bescosystems.com

sales@bescosystems.com