



Model 60 S Vertical Downstroke Baler

- HEAVY DUTY
STRUCTURAL FRAME
- ETL & UL LISTED/ANSI
Z245.5 COMPLIANT
- POWDER COATING ON
ALL STRUCTURAL PARTS
FOR A MORE DURABLE
AND LONG LASTING
FINISH WITH ANTI-
CORROSIVE PROPERTIES

Baler Dimensions

Height: 142" Width: 79" Depth: 38"



BUILT LIKE NO OTHER . . .

***2 YEAR LIMITED WARRANTY
BEST IN THE INDUSTRY***

MODEL 60S VERTICAL DOWNSTROKE BALER

SPECIFICATIONS

LARGE FEED OPENING
(26" H X 60")

PUMP
15 GPM GEAR PUMP

CYCLE TIME 32 SECONDS –
FASTEST IN THE INDUSTRY

MOTOR
15HP
208V/230V/480V 3 PH

48" LOADING HEIGHT

PLATEN WITH 4 CORNER GUIDES
LINED UHM WEAR STRIPS (REPLACEABLE)
PULL DOWN SAFETY GATE WITH CHAINS

CYLINDER
WELDED INDUSTRIAL
6" BORE
3 1/2" ROD
42" STROKE

DOOR HINGES AND WHEEL LOCK COATED FILM

18 LARGE HOLD DOWN DOGS, FRONT AND REAR

SYSTEM PRESSURE
2,000 PSI

AUTOMATIC CYCLE OPERATION
AUTOMATIC FULL BALE SHUTOFF

COMPACTING FORCE
56,548 lbs

CAPABLE OF BALING OCC, PAPER, CLOTH,
SHRINK WRAP, FOAM, AND NON-FERROUS METALS

EJECTOR SYSTEM
SEMI-AUTOMATIC
2 HEAVY DUTY CHAINS
AUTOMATIC DROP OFF

WARRANTY FOR 1 YEAR OR 2,080 HOURS,
WHICHEVER COMES FIRST, ON PARTS AND LABOR;
2 YEARS OR 4,160 HOURS WHICHEVER COMES FIRST
ON ALL PARTS REPLACEMENT.

BALE SIZE - 60" X 30" X 48"
BALE WEIGHT 1000lbs.-OCC

QUALITY BILT EQUIPMENT

1513 North Cameron Street

Harrisburg, PA 17103

1-888-773-9313 – toll free

1-717-238-9825 – fax

www.qualitybilt.com

sales@qualitybilt.com