



Model 60XHD Vertical Downstroke Baler



- HEAVY DUTY STRUCTURAL FRAME
- ETL & UL LISTED/ANSI Z245.5 COMPLIANT

Baler Dimensions

Height: 156" Width: 79" Depth: 38"

BUILT LIKE NO OTHER . . .

2 YEAR LIMITED WARRANTY BEST IN THE INDUSTRY

Quality Bilt 60XHD

SPECIFICATIONS

LARGEST FEED OPENING IN THE INDUSTRY
(28" H X 60")

PUMP

15 GPM GEAR PUMP

CYCLE TIME 59 SECONDS –
FASTEST IN THE INDUSTRY

MOTOR

20HP

230V 3 PH 51.2 FL AMPS

480V 3 PH 25.6 FL AMPS

48" LOADING HEIGHT

PLATEN WITH 4 CORNER GUIDES
LINED UHM WEAR STRIPS (REPLACEABLE)
PULL DOWN SAFETY GATE WITH CHAINS

CYLINDER

WELDED INDUSTRIAL

7" BORE

5" ROD

60" STROKE

DOOR HINGES AND WHEEL LOCK COATED FILM

24 LARGE HOLD DOWN DOGS, FRONT AND REAR

SYSTEM PRESSURE

2,100 PSI

AUTOMATIC CYCLE OPERATION
AUTOMATIC FULL BALE SHUTOFF

COMPACTING FORCE

80,819 PSI

CAPABLE OF BALING OCC, PAPER, CLOTH,
SHRINK WRAP, FOAM, AND NON-FERROUS METALS

EJECTOR SYSTEM

SEMI-AUTOMATIC

2 HEAVY DUTY CHAINS

AUTOMATIC DROP OFF

WARRANTY FOR 1 YEAR OR 2,080 HOURS,
WHICHEVER COMES FIRST, ON PARTS AND LABOR;
2 YEARS OR 4,160 HOURS WHICHEVER COMES FIRST
ON ALL PARTS REPLACEMENT.

BALE SIZE - 60" X 30" X 48"
BALE WEIGHT upto 1300lbs.-OCC

www.qualitybilt.com